

Friedrich®

Uni-Fit®

Universal Thru-the-wall Air Conditioners

Universal fit for easy replacement. Chassis installs into many competitive sleeves with included accessories. Quiet and energy efficient.

- High efficiency operation saves on energy costs
 - Rotary compressors provide quiet, dependable performance
 - Cooling only and cooling with electric heat models available
 - 4-way air flow control
 - Stale air exhaust
 - Permanent filter
 - Seacoast protection
- COOLING MODELS feature electronic controls with remote and 3 cooling/ 2 fan-only speeds
 - HEAT/COOL MODELS feature 2 cooling and 2 heating speeds, plus 2 fan-only settings



8,000 to 11,700 BTU/h
115 and 230/208 volt
EERs up to 10.0

***IMPORTANT NOTE:** Sleeves are sold and shipped separately to accommodate new construction and replacement requirements*



NEW! Electronic cooling models

- Remote control
- Programmable timer
- Money Saver® setting
- Dry Mode

AMERICA'S BEST AIR CONDITIONER

Uni-Fit® Universal Thru-the-wall

MODEL		US08B10	UE08A13A	US10B10	US10B30	UE10A33A	US12B10	US12B30	UE12A33A
Performance									
BTU/h	(Cooling)	8000	8000	10000	10000/9800	10000/9800	11700	11700/11400	11700/11400
	(Electric Heating)	None	3850	None	None	11200/9200	None	None	11200/9200
EER		10.0	10.0	9.5	9.5/9.5	9.5/9.5	9.5	9.5/9.5	9.5/9.5
COP		None	None	None	None	None	None	None	None
Dehumidification	(Pts/Hr)	2.2	2.2	3.0	3.0	3.0	3.5	3.5	3.5
Dry Air Flow	(CFM) H / M / L	220/205/190	220/205/190	240/225/210	240/225/210	240/225/210	255/240/225	255/240/225	255/240/225
dBA Level	(Indoor / Outdoor)	48/58	48/58	50/59	50/59	51/60	51/60	51/60	52/60
Electrical Ratings									
Voltage / 60 Hz		115	115	115	230/208	230/208	115	230/208	230/208
Watts	(Cooling)	800	800	1050	1050/1030	1050/1030	1230	1230/1200	1230/1200
	(Electric Heating)	None	1230	None	None	3500/2900	None	None	3500/2900
Rated Amps	(Cooling)	7.5	7.5	9.8	4.7/5.2	4.7/5.2	11.5	5.8/6.2	5.8/6.2
	(Electric Heating)	None	10.7	None	None	15.3/14.0	None	None	15.3/14.0
Features									
Control Type		ELECTRONIC	ROTARY	ELECTRONIC	ELECTRONIC	ROTARY	ELECTRONIC	ELECTRONIC	ROTARY
Remote Control		Yes	—	Yes	Yes	—	Yes	Yes	—
Open Inlet Grille		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Thermostat Control		Thermistor	Thermostat	Thermistor	Thermistor	Thermostat	Thermistor	Thermistor	Thermostat
Air Deflection		4-WAY	4-WAY	4-WAY	4-WAY	4-WAY	4-WAY	4-WAY	4-WAY
Fan Speeds:	Cooling / Heating	3	2 / 2	3	3	2 / 2	3	3	2 / 2
	Fan Only	2	2	2	2	2	2	2	2
Compressor		ROTARY	ROTARY	ROTARY	ROTARY	ROTARY	ROTARY	ROTARY	ROTARY
Type Air Discharge		TOP	TOP	TOP	TOP	TOP	TOP	TOP	TOP
Stale Air Exhaust		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Trim Kit		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Accessory Kit for Sealing		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Sleeve & Rear Grille									
Sleeve with Expanded Aluminum Rear Grille		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Dimensions and Weight									
Chassis	Height (inches)	14 13/32	14 13/32	14 13/32	14 13/32	14 13/32	14 13/32	14 13/32	14 13/32
	Width (inches)	24 21/32	24 21/32	24 21/32	24 21/32	24 21/32	24 21/32	24 21/32	24 21/32
	Depth with front grille (inches)	19 21/32	19 21/32	19 21/32	19 21/32	19 21/32	19 21/32	19 21/32	19 21/32
Sleeve	Height (inches)	15 17/32	15 17/32	15 17/32	15 17/32	15 17/32	15 17/32	15 17/32	15 17/32
	Width (inches)	25 7/8	25 7/8	25 7/8	25 7/8	25 7/8	25 7/8	25 7/8	25 7/8
	Depth (inches)	16 23/32	16 23/32	16 23/32	16 23/32	16 23/32	16 23/32	16 23/32	16 23/32
	Depth with front grille (inches)	20	20	20	20	20	20	20	20
Net Weight	w/o Sleeve (lbs.)	72	73	79	80	80	80	80	81
Shipping Weight	w/o Sleeve (lbs.)	79	79	86	86	87	87	87	87

Sleeve Dimensions of Major Brands		Friedrich Uni-Fit®	GE	Amana	Whirlpool Fedders	Frigidaire
Height	(inches)	15 17/32	15 5/8	15 5/8	15 3/4	15 7/16
Width	(inches)	25 7/8	26	26	26 3/4	25 7/8
Depth	(inches)	16 23/32	16 7/8	16 7/8	15	18

Model	Circuit Rating Breaker or TD Fuse	Plug Face (NEMA#)	Appearance (Facing Blades)
US08B10, UE08A13A	125-15A	5-15P	
US10B10, US12B10			
US10B30, US12B30	250V-15A	6-15P	
UE10A33A, UE12A33A			
	250V-20A	6-20P	



Friedrich Air Conditioning Co.
www.friedrich.com

Post Office Box 1540
San Antonio, Texas 78295-1540
Phone: 1-800-541-6645 Fax: 1-210-357-4480

UTW-04



Printed in USA